

Smart Door Lock C100

LifeSmart

Highlights

- Ultra-thin panel design.
- Use the advanced fingerprint reader, excellent at distinguish fake and shallow fingerprint.
- Ultra clear digital intelligent touch screen.
- High performance integrated chip, fast response, better experience.
- Fingerprint is on the handle, door opening is more easy and convenient.
- The cat-proof mechanical dial button design prevents the technology tools from turning on.

Features

Bezel-less Tempered Glass Panel | Touch panel is made of tempered glass and embed within the body for durable protection.

Multiple Ways for Access | You can open your door with fingerprint, password, NFC card, a traditional key or through LifeSmart App.

Anti-Peeping Password | You only need to enter the correct password contained in the last 64 digits to open the door. And it can prevent the password from peeping.

Anti-Hijacking Password | You can pre-set your hostage password. When an abduction happens, just input your hostage password to inform your family for help.

Description

The LifeSmart Smart Door Lock C100 has 5 unlocking methods: fingerprint recognition, password, Mifare card, mechanical key and through LifeSmart App. With the super class C lock cylinder and 304 stainless steel lock body, it support high security level. At the same time, it support tamper alarm, anti-peeping password, peep hole anti-unlock and other functions. Make you safe and worry-free every time you open the door.



BASIC SPECIFICATION

Unlocking ways	Fingerprint/ Password/ Mifare card/ Mechanical key/ LifeSmart App
Color	Black
Material	Aluminum alloys
Product Size	363mm*73mm*23mm
Radio Protocol	CoSS
Radio Range	100m (Open Field)
User Capacity	99 groups
Fingerprint Reader	Semiconductor sensor
Password Input	Touch key
Password Function	Virtual password; Password protection
Chip System	Dual CPU and dual system
Fingerprint Identification Time	< 0.5s
Up-down Hook	Support
Cylinder Lock	Grade C
Mechanical Keys	2
Working Power	4*1.5V AA Alkaline Battery
Working Environment	-25°C-55°C
Suitable Door Thickness	46-115mm
Suitable Lock Body	J6068 (Standard)



Smart Door Lock C100

